

Tinytag Input Leads

CAB-3239, CAB-3246 & CAB-3233

CAB-3239 Tinytag Voltage/Current Input Lead



For use with: TE-4703, TE-4704, TE-4743, TE-4744
 TGP-4703, TGP-4704, TGP-4804, TGPR-0704
 TV-4703, TV-4704, TV-4804
 TGRF-4703, TGRF-4704, TGRF-4743, TGRF-4744
 TR-3703, TR-3704

Cable Length: 1.5m
 Weight: 60g
 Material: PVC
 Temp Rating: -10 to +85°C
 IP Rating: IP68 (Connector)

CONNECTION INFORMATION

Colour	Pin	Function
Red	A	DO NOT CONNECT
Green	B	N/C
White	C	Sense Line
Black	D	Common/0V
Yellow	E	Signal Input

CAB-3246 Tinytag Current, Millivolt, Count Input Lead



For use with: TE-4804, TE-4844, TE-4901, TE-4904
 TGP-4901
 TGPR-0804, TGPR-1001, TGPR-1201
 TGRF-4804, TGRF-4844, TGRF-4901,
 TGRF-4904
 TR-1201, TR-3804

Cable Length: 1.5m
 Weight: 35g
 Material: PVC
 Temp Rating: -10 to +85°C
 IP Rating: IP68 (Connector)

CONNECTION INFORMATION

Colour	Pin	Function
Blue	A	Common/0V
Red	B	Signal Input

CAB-3233 Talk Voltage/Current Input Lead



For use with: TK-4702, TK-4703, TK-4802

Cable Length: 1.5m
 Weight: 27g
 Material: PVC
 Temp Rating: -10 to +85°C
 IP Rating: IP30 (Not Waterproof)

CONNECTION INFORMATION

Colour	Jack Plug	Function
White	Tip	Sense Line
Yellow	Ring	Signal Input
Black	Shank	Common/0V

Approvals

Gemini Data Loggers (UK) Ltd. operates a Business Management System which conforms to ISO 9001 and ISO 14001.

